

ACON U 03
USB TO RS232 CONVERTER
NON-ISOLATED



INTRODUCTION: The model is USB bus power, high speed, USB to RS232 converter. It supports AUTO baud rate. The model supports for RS 232.

SPECIFICATIONS:

INTERFACE	: USB TO RS 232
OPERATION	: USB TO RS 232
SIGNAL PINS	: TX, RX, RTS/CTS, DSR/DTR.
SPEED	: 2400 TO 115 Kbps
CONNECTORS	: 1) USB – USB 'A' TYPE FEMALE CONNECTOR 2) RS232 DB9 MALE
INDICATIONS	: POWER, TX, RX,
POWER	: USB BUS POWER
CASE	: PLASTIC ENCLOSURE
SIZE	: 70mm x 33mm x 15mm.
OPERATING TEMP	: 0 – 70 C
POWER CONSUMPTION	: 1W
HUMIDITY	: 5 – 95% NON CONDENSING
ACCESSORIES	: DRIVER CD



CONNECTION DETAILS:

DB9 MALE RS – 232

PIN NO 2 ----- RX
PIN NO 3 ----- TX
PIN NO 7 ----- RTS
PIN NO 8 ----- CTS
PIN NO 6 ----- DSR
PIN NO 4 ----- DTR

Address: Narhe Industrial Estate, Lane No. 1, Sr. No. 44/21, Narhe Gaon, Tal-Haveli, Pune, Maharashtra 411041 **Tel :** +91 9284025858

Email: Info@abacuselectronics.in **Webiste:** www.abacuselectronics.in